

E Flood Light

A5

·Universal Application



A5
E Flood Light



1. Features

- High Quality with Precision Die Cast Aluminum Housing
- Easy Installation
- Streamline exterior design, beautiful appearance
- Environmentally friendly alternative to traditional lighting
- Lifetime over 50,000hours

2. Technical Specifications

Input Voltage:	AC100-265V/AC170-265V
Watts:	50W, 100W, 200W, 300W, 400W, 600W, 800W, 900W
Beam Angle:	60°/120°
Colour Temperature:	2800-6500K
CRI:	CRI>75
Driver:	Meanwell
LED Type:	Philips 3030



3. Parameter

Item Code	Power(W)	Lumens	Size(mm)
LU-FLE-50W	50W	5000LM	209*202*31
LU-FLE-50W*2	100W	10000LM	418*202*31
LU-FLE-50W*4	200W	20000LM	418*404*31
LU-FLE-50W*6	300W	30000LM	418*608*31
LU-FLE-50W*8	400W	40000LM	819*404*31
LU-FLE-100W	100W	10000LM	220*270*34
LU-FLE-200W	200W	20000LM	455*237*56
LU-FLE-200W*2-A	400W	40000LM	455*474*56
LU-FLE-200W*2-B	400W	40000LM	915*237*56
LU-FLE-200W*3	600W	60000LM	715*455*56
LU-FLE-200W*4-A	800W	80000LM	955*455*56
LU-FLE-200W*4-B	800W	80000LM	455*915*56
LU-FLE-300W	300W	30000LM	670*236*56
LU-FLE-300W*2	600W	60000LM	474*670*56
LU-FLE-300W*3	900W	90000LM	474*670*56

